

## Data sheet: die set 624 339

Crimping cavity	1	2	3	4
Cable cross section	1,00 mm <sup>2</sup>	1,50 mm <sup>2</sup>	1,50 mm <sup>2</sup>	2,50 mm <sup>2</sup>
Crimping height	1,34 mm	1,48 mm	1,69 mm	1,97 mm
Height tolerances	± 0,05 mm	± 0,05 mm	± 0,05 mm	± 0,05 mm
Step	-	-	-	-
Wire crimping width	2,34 mm	2,40 mm	2,46 mm	2,48 mm
Width tolerance	± 0,10 mm	± 0,10 mm	± 0,10 mm	± 0,10 mm
Insulation crimping height	3,75 mm	3,84 mm	3,98 mm	4,19 mm
Insulation crimping width	3,82 mm	3,82 mm	4,05 mm	4,27 mm
Seal	281934	281934	281934	281934
Special aspects	-	-	-	-
PN Strip			<b>Tyco Electronics</b> <b>Mini Mic Superseal 1.5</b> 183021, 282465, 282466	<b>Tyco Electronics</b> <b>Mini Mic Superseal 1.5</b> 183021, 282465, 282466
PN Loose	<b>Tyco Electronics</b> <b>Mini Mic Superseal 1.5</b> 183024		<b>Tyco Electronics</b> <b>Mini Mic Superseal 1.5</b> 183022	<b>Tyco Electronics</b> <b>Mini Mic Superseal 1.5</b> 183022

## Tools

