

Data sheet: die set 624 773

Crimping cavity	1	2	3	4
Cable cross section	0,35 - 0,50 mm ²	0,75 mm ²	1,00 mm ²	1,50 mm ²
Crimping height	1,00 mm	1,29 mm	1,37 mm	1,53 mm
Height tolerances	± 0,05 mm	± 0,05 mm	± 0,05 mm	± 0,05 mm
Step	-	-	-	-
Wire crimping width	2,03 mm	2,29 mm	2,29 mm	2,29 mm
Width tolerance	± 0,10 mm	± 0,10 mm	± 0,10 mm	± 0,10 mm
Insulation crimping height	3,90 mm	3,70 mm	3,80 mm	3,90 mm
Insulation crimping width	4,06 mm	4,06 mm	4,06 mm	4,06 mm
Seal	281934-4	281934-2	281934-2	281934-2
Special aspects	-	-	-	-
PN Strip	Tyco Electronics Mini Mic Superseal 1.5 282403, 282404	Tyco Electronics Mini Mic Superseal 1.5 282109, 282110	Tyco Electronics Mini Mic Superseal 1.5 282109, 282110	Tyco Electronics Mini Mic Superseal 1.5 282109, 282110
PN Loose	Tyco Electronics Mini Mic Superseal 1.5 183035, 183036	Tyco Electronics Mini Mic Superseal 1.5 183024, 183025	Tyco Electronics Mini Mic Superseal 1.5 183024, 183025	Tyco Electronics Mini Mic Superseal 1.5 183024, 183025

Tools

